



**630 mm x 850 mm x 50 mm SKF 292/630 EM
Axial roller bearing**

Bearing No. 292/630 EM

292/630 EM Bearing 2D drawings and 3D CAD models

| | |
|---|----------------|
| Size | 850x630x132 mm |
| Bore Diameter | 850 mm |
| Outer Diameter | 630 mm |
| Width | 132 mm |
| d | 630 mm |
| D | 850 mm |
| H | 132 mm |
| d ₁ | 810 mm |
| D ₁ | 723 mm |
| B | 50 mm |
| B ₁ | 127 mm |
| C | 62 mm |
| s | 338 mm |
| r _{1,2} - min. | 6 mm |
| d _a - min. | 740 mm |
| D _a - max. | 780 mm |
| r _a - max. | 5 mm |
| Basic dynamic load rating - C | 4770 kN |
| Basic static load rating - C ₀ | 23600 kN |
| Fatigue load limit - P _u | 1800 kN |
| Reference speed | 400 r/min |
| Limiting speed | 670 r/min |
| Factor min. axial load - A | 53 |
| d ₁ | 810 mm |



NTN BEARING MANUFACTURING DE MEXICO,S...

| | |
|--------------------------------|----------|
| D_1 | 723 mm |
| B_1 | 127 mm |
| $r_{1,2}$ min. | 6 mm |
| d_a min. | 740 mm |
| D_a max. | 780 mm |
| r_a max. | 5 mm |
| Basic dynamic load rating C | 4770 kN |
| Basic static load rating C_0 | 23600 kN |
| Fatigue load limit P_u | 1800 kN |
| Minimum axial load factor A | 53 |
| Mass bearing | 210 kg |